




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷: E21B 4/00, F16C 27/08, 35/06	A1	(11) International Publication Number: WO 00/46478 (43) International Publication Date: 10 August 2000 (10.08.00)
(21) International Application Number: PCT/GB00/00314 (22) International Filing Date: 3 February 2000 (03.02.00) (30) Priority Data: 9902253.5 3 February 1999 (03.02.99) GB (71) Applicant (for all designated States except US): ROTECH HOLDINGS LIMITED [GB/GB]; Whitemyres Avenue, Mastrick Industrial Estate, Aberdeen AB2 6HQ (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): SUSMAN, Hector, Fillipus [GB/GB]; Alexander Van Drentham, 9 Craigston Gardens, Westhill Estate, Aberdeen AB32 6NL (GB). (74) Agents: McCALLUM, William, Potter et al.; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: THRUST BEARING FOR DOWN-HOLE TOOL



(57) Abstract

There is disclosed an improved bearing and particularly an improved bearing assembly (15, 15A), eg. a thrust bearing assembly, which may be used in down-hole applications, such as down-hole drilling applications. Thrust bearing assemblies for use in down-hole applications have the conflicting requirements of a thick shaft assembly and high axial load bearing capacity in a small crosssection. The invention, therefore, provides: a bearing assembly (15, 15A) having at least two bearing elements (400, 400A) spaced by a first body (500, 500A), the first body (500, 500A) having means for flexing. Thus when a load is applied to the bearing assembly (15, 15A) the first body (500, 500A) is caused to flex. In an embodiment the flexing means comprise at least one circumferential groove or notch (510, 510A) formed on the first body (500, 500A).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

THRUST BEARING FOR DOWHOLE TOOL

This invention relates to an improved bearing. Particularly, though not exclusively, the invention relates to an improved bearing assembly, eg. a thrust bearing assembly, which may be used in down-hole applications, eg. down-hole drilling applications, such as in the oil/gas production industries.

Thrust bearing assemblies for use in down-hole applications have the conflicting requirements of a thick shaft assembly and high axial load bearing capacity in a small cross-section. To achieve this a number of thrust bearings may be mounted in line to provide sufficient load and shock capacity. In conventional bearing assemblies this introduces a problem as the load may not be shared equally between the series of bearings which may result in excessive wear or failure of one or more of the bearings. This problem can be mitigated by use of assemblies of springs and spacers. However, these tend to be complex in nature. An additional problem in down-hole apparatus is that space tends to be limited.

It is an object of at least one aspect of the present invention to obviate or mitigate the aforementioned problems in the prior art.

It is a further object of at least one embodiment of at least one aspect of the present invention to seek to provide a flexible, load sharing, anti-friction bearing assembly/unit.

According to a first aspect of the present invention there is provided a bearing assembly having at least two bearing elements spaced by a first body, the first body having means for flexing.

5 Thus when a load is applied to the bearing assembly the first body may be caused to flex.

Advantageously the flexing means may comprise at least one groove or notch formed on the first body.

10 Preferably the first body is substantially annular in shape, the at least one groove preferably being formed on an outer surface of the first body.

Advantageously the groove is substantially U-shaped.

The first body may be rigidly mounted to a body to which load is applied, in use.

15 Preferably a first annular surface of the first body is provided with a first annular raceway.

Preferably also, a second annular surface of the first body is provided with a second annular raceway.

20 Advantageously the first and second bearing elements each comprise a plurality of balls, the first and second bearing elements preferably being received for movement within the first and second annular raceways of the first body.

25 In a preferred arrangement the means for flexing flexes about a longitudinal axis of the first body.

Further, in the preferred arrangement the groove is provided substantially circumferentially around the first body.

According to a second aspect of the present invention there is provided a bearing assembly having at least two bearing elements spaced by a first body, the first body being at least partly flexible.

5 According to a third aspect of the present invention there is provided a bearing unit comprising at least one and preferably a plurality of bearing assemblies according to the first aspect.

10 Advantageously each adjacent bearing assembly are spaced by a second body.

Preferably the second body is substantially annular in shape.

The second body may be rigidly mounted to a further body to which load is not (directly) applied in use.

15 Preferably a first annular surface of the second body is provided with a first annular raceway.

Preferably also, a second annular surface of the second body is provided with a second annular raceway.

20 Advantageously, respective first and second bearing elements may be received for movement within the first and second annular raceways of the second body.

Advantageously, adjacent first bodies are spaced by a respective first spacer element.

25 Advantageously also, adjacent second bodies are spaced by a respective second spacer element.

In one embodiment a further first spacer element may be provided between an end to which force is applied, in use, and an adjacent end of an adjacent first body.

According to a fourth aspect of the present invention there is provided a tool or apparatus including a bearing assembly according to the first aspect of the present invention or a bearing unit according to the second aspect of the present invention.

The tool may be a down-hole tool, eg. for use in a borehole of an oil/gas well.

The tool may comprise part of a borehole drilling apparatus, which may include a down-hole motor such as a Mointeau motor or a motor as disclosed in WO95/19488, the content of which is incorporated herein by reference.

The first body may be rigidly mounted to a shaft to which load is applied, in use.

The shaft may be contained substantially concentrically within the bearing assembly/unit.

The second body may be rigidly mounted to a housing.

The housing may substantially concentrically surround the bearing assembly/unit.

Advantageously, adjacent first bodies are longitudinally spaced by a first spacer element, which may also be mounted on the shaft.

Advantageously also, adjacent second bodies are longitudinally spaced by a second spacer element, which may also be mounted on the housing.

Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings, which are:

Fig. 1 a cross-sectional side view of a portion of a

down-hole tool including a bearing assembly according to a first embodiment of the present invention.

Fig. 2 a perspective view of a portion of the bearing assembly of Fig. 1.

5 Fig. 3 a cross-sectional side view of a down-hole tool including a bearing assembly according to a second embodiment of the present invention.

Referring initially to Fig. 1 there is illustrated a portion of a down-hole tool, generally designated 5,
10 according to a first embodiment of the present invention. The tool 5 may take the form of a borehole drilling apparatus. The tool 5 includes a bearing unit (pack) 10 comprising a series of adjacent bearing assemblies 15 - in this embodiment three assemblies 15 are provided.

15 Each bearing assembly 15 has two anti-friction bearing elements 400 spaced by a first body 500, the first body 500 having means for flexing. Thus, when a load is applied to the bearing assembly 15, the first body 500 is caused to flex. In this embodiment the flexing means comprise at
20 least one substantially circumferentially formed groove 510 formed on the first body 500.

The first body 500 is substantially annular in shape, the at least one groove 510 being formed on an outer surface of the first spacer body 500. As can be seen from
25 Figs. 1 and 2 the groove 510 is substantially U-shaped in side cross-section.

The first body 500 is rigidly mounted to a shaft 600 to which load is applied, in use, the shaft 600 being

substantially concentrically contained within the bearing unit 10. The shaft 600 may be hollow and may have a socket 610 for connection, eg. to a drill bit or the like (not shown).

5 A first annular surface 610 of the first body 500 is provided with a first raceway 620. Further a second annular surface 630 of the first body 500 is provided with a second annular raceway 640. The first and second bearing elements 400 each comprise a plurality of balls, the first
10 and second bearing elements 400 being received for movement within the first and second annular raceways 620, 640 of the first body 500.

 The bearing unit 10 comprises a plurality of bearing assemblies 15. Each adjacent bearing assembly 15 are
15 spaced by a second body 200. Each second body 200 is substantially annular in shape. The second bodies 200 are rigidly mounted to an outer housing 100 to which load is not (directly) applied, in use.

 A first annular surface 650 of each second body 200 is
20 provided with a first annular raceway 660. A second annular surface 670 of each second bodies 200 provided between adjacent assemblies 15 is provided with a second annular raceway 680. Second bodies 200 provided at ends of the unit 10 are only provided with one raceway 660 - as can
25 be seen from Fig. 1.

 In this way respective first and second bearing elements 400 are received for movement within the first and second annular raceways 660, 670 of the second spacer body

200.

Referring to Fig. 1 the second bodies 200 are rigidly mounted to a housing 100. The housing 100 substantially concentrically surrounds the bearing unit 10.

5 A first raceway 620 of the first spacer body 500 faces a second raceway 680 of a second body 200. Similarly a second raceway 640 of the first body 500 faces a first raceway 660 of a second body 200.

10 As can be seen from Fig. 1 the first bodies 500 are longitudinally spaced along the shaft 600 and separated by first spacer elements 700 which may be rigidly mounted to the shaft 600. Further as can be seen from Fig. 1 the second bodies 200 are longitudinally spaced along the housing 100 and separated by second spacer elements 300
15 which may be rigidly mounted to the housing 100.

It is noted that the shaft 600 is free to rotate relative to the housing 100. Thus the first bodies 500 may rotate relative to the second bodies 200.

20 The components of the tool 5 may, in this embodiment be made from the following materials:

housing 100	- steel
second bodies 200	- hardened steel
second spacer elements 300	- steel
bearing elements 400	- hardened steel
	and/or ceramic
25 first spacer bodies 500	- hardened steel
shaft 600	- steel
first spacer elements 700	- steel

However, it will be appreciated that one may use any alloy steel capable of surface hardening to a case depth in the order of 10 thousandths of an inch by nitriding/carborising.

5 In use, the flexibility of bearing assembly 15 provides load sharing throughout the bearing unit 10. This flexibility is imparted by the grooves 510. As a (thrust) load F is applied to the shaft 600, a first body 500 deflects or flexes under the load F seeking to ensure that
10 the next first bodies 500 are suitably positioned such that some of the load is then transferred through the adjacent inner spacer 700 to the next first body 500 and so on. This seeks to ensure that the load F is spread evenly between the bearing assemblies 15 in the unit 10, and is
15 not supported by a single bearing assembly 15. Thus the load F is distributed in a way which is not possible using known rigid bearing assemblies. As each body 200, 500 is double sided the load F may be either tensile or compressive. In either case the load F will be shared over
20 each of the bearing assemblies 15 of the unit 10.

Both static and dynamic tests have been carried out on 1 11/16 inch flexible bearing unit 10 and its performance has been found to be even better than expected.

25 The bearing assembly 15 showed a linear deflection to 20kN where shortly thereafter Brinelling occurred. This was then followed by a second linear deflection as both flexing of the horseshoe shaped groove 510, and to a lesser extent Brinelling continues. Deflection is 0.8mm before

Brinelling occurs per bearing assembly 15, whereas predictions suggested 0.05 to 0.06mm, an increase by a factor of 15. There was no damage to the bearing elements on any occasion.

5 From inspection of the raceways 620, 640 after testing, it was found that the load is applied at approximately 45 degrees towards shoulders of the raceways 620, 640 ie. away from the flexible portion, and is not vertical. The result is a much stronger bearing assembly
10 15 as it only has to cope with around 0.707 times the vertical force supplied, thus being able to carry more load. This load is also directed into the strongest and stiffest part of the raceways further increasing the load carrying capabilities.

15 For a bearing unit 10, each raceway can withstand in the region of 25kN before significant damage occurs. For example, for 5 sets of raceways, the load before any serious problems would occur is approximately 125kN or 12.7 tonnes, which far exceeds what is expected in the field.

20 The load is shared to a high degree after initial Brinelling of a first body raceway. However, under very high loads the raceway nearest the load deteriorates quicker and the subsequent failure propagated the load to the remaining raceways.

25 The Brinelling effect seen on the face of the first raceway does not deteriorate under higher loads.

 The combination of the two dynamic tests using optimised spacers lasted for 219.5 hours at 1500 lbf WOB.

Considering that a conventional 1 11/16" MACDRILL (TM) motor as discussed in WO95/19488 has a stall torque at this force, it can be safe to assume that this load will not be seen for sustained periods when drilling. Bearing in mind, and the fact that the load to wear curve is exponential, the life expectancy of the flexible bearing unit 10 at normal operating loads could be substantially greater than the 219.5 hours, of which it was subjected to during tests.

In summary the flexible bearing assemblies 15 are much stronger than were thought as the load is acting at 45° through the raceways. The load path with (WOB) loading carries the load in towards the shaft 600 and not towards the horseshoe shaped grooves 510. This therefore results in the raceway flexing less than its design specification and subjected to Brinelling rather than flex actions. The bearing unit 10 produces the same effect as in known angular contact bearings but at a fraction of the cost.

There are a number of options that can improve the design of the bearing unit 10 so that the initial Brinelling on a first inner spacer can be reduced, eg:

1. Increase the groove 510 depth to increase the flex and assist in load sharing.;
2. Incorporate an extra inner spacer to ensure the spring rate on the first body raceway and the rest of the raceways are the same.

Referring now to Fig. 3, there is illustrated a portion of a downhole tool, generally designated 5A, according to a second embodiment of the present invention.

The tool 5A is similar to the tool 5 of the first embodiment, like parts being denoted by like integers but suffixed 'A'. However, the tool 5A differs from the tool 5 in providing a extra inner spacer 700'A so as to seek to provide the advantage offered by (2) above.

It will be appreciated that the embodiments of the present invention hereinbefore described are given by way of example only, and are not meant to limit the scope of the invention in any way. It will, for example, be understood that the number of bearing assemblies forming a bearing unit may be selected to provide a desired load capacity.

It will further be appreciated that the present invention provides for a greater outer diameter of shaft therefore a larger (hex) coupling and therefore a higher torque capacity than known bearing unites. A greater outer diameter of shaft allows - for the same strength - a greater inner diameter of shaft and thus reduced pressure loss through the (drive) shaft.

20

CLAIMS

1. A bearing assembly having at least two bearing elements spaced by a first body, the first body having means for flexing.
5
2. A bearing assembly as claimed in claim 1, wherein, in use, when a load is applied to the bearing assembly the first body is caused to flex.
10
3. A bearing assembly as claimed in either of claims 1 or 2, wherein the flexing means comprise at least one groove or notch formed on the first body.
- 15 4. A bearing assembly as claimed in any of claims 1 to 3, wherein the first body is substantially annular in shape, the at least one groove being formed on an outer surface of the first body.
- 20 5. A bearing assembly as claimed in either of claims 3 or 4, wherein the groove is substantially U-shaped.
6. A bearing assembly as claimed in any preceding claim, wherein the first body is rigidly mounted to a body to
25 which load is applied, in use.

7. A bearing assembly as claimed in any preceding claim, wherein a first annular surface of the first body is provided with a first annular raceway.
- 5 8. A bearing assembly as claimed in claim 7, wherein a second annular surface of the first body is provided with a second annular raceway.
- 10 9. A bearing assembly as claimed in claim 8, wherein the first and second bearing elements each comprise a plurality of balls, the first and second bearing elements being received for movement within the first and second annular raceways of the first body.
- 15 10. A bearing assembly as claimed in any preceding claim, wherein the means for flexing flexes about a longitudinal axis of the first body.
- 20 11. A bearing assembly as claimed in any of claims 4 to 10 when dependent upon claim 3, wherein the groove is provided substantially circumferentially around the first body.
- 25 12. A bearing assembly having at least two bearing elements spaced by a first body, the first body being at least partly flexible.

14

13. A bearing unit comprising at least one bearing assembly according to any of claims 1 to 12.

14. A bearing unit as claimed in claim 13, wherein adjacent bearing assemblies are spaced by a second body.

15. A bearing unit as claimed in claim 14, wherein the second body is substantially annular in shape.

16. A bearing unit as claimed in claim either of claims 14 or 15, wherein the second body is rigidly mounted to a further body to which load is not (directly) applied in use.

17. A bearing unit as claimed in claim any of claims 14 to 16, wherein a first annular surface of the second body is provided with a first annular raceway.

18. A bearing unit as claimed in claim 17, wherein a second annular surface of the second body is provided with a second annular raceway.

19. A bearing unit as claimed in claim 18, wherein respective first and second bearing elements are received for movement within the first and second annular raceways of the second body.

20. A bearing unit as claimed in claims 13 to 19, wherein adjacent first bodies are spaced by a respective first spacer element.

5

21. A bearing unit as claimed in claim any of claims 13 to 20, wherein adjacent second bodies are spaced by a respective second spacer element.

10

22. A bearing unit as claimed in claim any of claims 13 to 21, wherein a further first spacer is provided between an end to which force is applied, in use and an adjacent end of an adjacent first body.

15

23. A tool or apparatus including a bearing assembly according to any of claims 1 to 12.

24. A tool or apparatus including a bearing unit according to any of claims 13 to 22.

20

25. A tool or apparatus as claimed in either of claims 23 or 24, wherein the tool is a down-hole tool, eg. for use in a borehole of an oil/gas well.

25

26. A tool or apparatus as claimed in any of claims 23 to 25, wherein the tool comprises part of a borehole drilling apparatus, which optionally includes a down-hole motor.

27. A tool or apparatus as claimed in any of claims 23 to 27, wherein the/a first body is rigidly mounted to a shaft to which load is applied, in use.

5 28. A tool or apparatus as claimed in claim 27, wherein the shaft is contained substantially concentrically within the bearing assembly/unit.

10 29. A tool or apparatus as claimed in claim 24 or any of claims 25 to 28 when dependent upon claims 23, wherein the second body is rigidly mounted to a housing.

15 30. A tool or apparatus as claimed in claim 29, wherein the housing is substantially concentrically surrounds the bearing assembly/unit.

20 31. A tool or apparatus as claimed in claim 24 or any of claims 25 to 30 when dependent upon claim 24 wherein adjacent first bodies are longitudinally spaced by a first spacer element.

25 32. A tool or apparatus as claimed in claim 31 when dependent upon claim 27, wherein the first spacer elements-is/are mounted on the shaft.

33. A tool or apparatus as claimed in claim 24 or any of claims 25 to 22 when dependent upon claim 24, wherein adjacent second bodies are longitudinally spaced by a


second spacer element.


34. A tool or apparatus as claimed in claim 33 when dependent upon claim 29, wherein the second spacer elements is/are mounted on the housing.

5

2/3

Fig.2.





INTERNATIONAL SEARCH REPORT

Internat Application No

PCT/GB 00/00314

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E21B4/00 F16C27/08 F16C35/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B F16C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CH 239 592 A (GERTSCH) 18 February 1946 (1946-02-18) page 1, left-hand column, line 12 - line 22	1-4, 7-13, 23
X	US 1 346 417 A (PALMGREN) 13 July 1920 (1920-07-13) page 1, line 41 - line 53 page 1, line 67 - line 82	1-4, 10-13
X	DE 938 343 C (ADOLF SCHNORR KG) 26 January 1956 (1956-01-26) figure 1	1, 12, 13, 23, 24
X	GB 1 344 318 A (SOCIETE NATIONALE D'ETUDE ET DE CONSTRUCTIONS DE MOTEURS D'AVIATION) 23 January 1974 (1974-01-23) figure 1	1, 12, 13, 23, 24

-/-

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

23 May 2000

Date of mailing of the international search report

29/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Rampelmann, K

INTERNATIONAL SEARCH REPORT

International Application No
 PCT/GB 00/00314

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 1 448 189 A (BRUNNER) 13 March 1923 (1923-03-13) page 2, line 6 - line 10 page 2, line 55 - line 62	1, 12, 13, 23, 24
A	US 4 220 380 A (CRASE) 2 September 1980 (1980-09-02) figure 2A	25
A	US 5 690 434 A (BESHOORY) 25 November 1997 (1997-11-25) figure 3	1
A	US 5 074 681 A (TURNER) 24 December 1991 (1991-12-24) figure 2	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/00314

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
CH 239592	A	NONE	
US 1346417	A	13-07-1920	NONE
DE 938343	C	NONE	
GB 1344318	A	23-01-1974	FR 2110693 A 02-06-1972 DE 2152309 A 04-05-1972
US 1448189	A	13-03-1923	NONE
US 4220380	A	02-09-1980	NONE
US 5690434	A	25-11-1997	NONE
US 5074681	A	24-12-1991	NONE